

SAFETY DATA SHEET

SDS No.1021-24204

Date

November 6, 2017

1/4 page

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : Butyl acetate
NAME OF SUPPLIER : GL Sciences Inc.
ADDRESS : 22-1 Nishishinjuku 6-chome Shinjuku-ku Tokyo 163-1130, Japan
CHARGE SECTION : International Sales Section
TELEPHONE No. : +81-3-5323-6620
FACSIMILE No. : +81-3-5323-6621
PRODUCT No. : 1021-24204
SDS No. : 1021-24204
Research use only.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION : Flammable liquid : Category 2
Eye damage/irritation : Category 2B
Specific target organ toxicity (Single exposure) : Category 3(respiratory irritation, an esthesia)
Hazardous to the aquatic environment - Acute hazard : Category 3

HAZARD SYMBOL :



SIGNAL WORD : Danger

HAZARD STATEMENTS :

H225 High flammable liquid and vapour
H320 Cause eye irritation
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H402 Harmful to aquatic life

PRECAUTIONARY STATEMENTS :

P210 Keep away from heat/sparks/open flames/hot surfaces. –No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapour/spray.
P271 Use only outdoors or in a well-ventilated area.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P273 Avoid release to the environment.
P303+P361+P353 IF ON SKIN or hair: Take off immediately all contaminated clothing. Rinse skin with water.
P370+P378 In case of fire: Use appropriate medias to extinguish.
P305+ P351+ P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical attention.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER or doctor if you feel unwell.
P403+ P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with all applicable regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL IDENTITY	: Butyl acetate
SYNONYMS	: n-Butyl acetate; Acetic acid, butyl ester; Butyl ethanoate
CONTENT	: > 99 %
CHEMICAL FORMULA	: CH ₃ COO(CH ₂) ₃ CH
MOLECULAR WEIGHT	: 116.16
CAS No.	: 123-86-4
TSCA INVENTORY	: Listed
EINECS No.	: 204-658-1
EC INDEX No.	: 607-025-00-1

4. FIRST AID MEASURES

GENERAL ADVICE	: Consult a physician. Show this safety data sheet to the doctor in attendance.
INHALATION	: Move victim to fresh air. If breathing is difficult, give oxygen. If irritation persists, consult a physician.
SKIN CONTACT	: Remove contaminated clothes and shoes, rinse skin with plenty of water or shower. Use soap to help assure removal. Consult a physician immediately.
EYE CONTACT	: Flush eyes well with flooding large amounts of running water for at least 15 minutes. Assure adequate flushing by separating the eyelids with sterile fingers. If possible, remove any contact lenses. Consult a physician immediately.
INGESTION	: Rinse mouth, give plenty of water to dilute the substance. Do not induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician immediately.
MOST IMPORTANT SYMPTOMS AND EFFECTS	: Inhalation; cough, sore throat, nausea, headache Contact to skin/eye; dry, pain, redness Digestion; vomiting

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA	: Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
FIRE & EXPLOSION HAZARDS	: Toxic, irritating, dust/fume/smoke may be emitted. Carbon monoxide may be foamed.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS	: Firemen should wear normal protective equipment(full bunker gear) and positive-pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	: Remove ignition sources and ventilate the area. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid raising dust and avoid contact with skin and eyes.
ENVIRONMENTAL PRECAUTIONS	: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.
METHODS FOR CLEAN UP	: Do not touch spilled material without suitable protection. Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

HANDLING	: Keep away from ignition sources and ventilate the area —No smoking. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with eyes, skin, and clothing. Avoid inhalation of vapour or mist. Avoid prolonged or repeated exposure. Handle this product with suitable protection. Wear protections when cutting ample and treating this product.
STORAGE	: Store away from sunlight, heat and all ignition sources in well-ventilated dry place. Keep container tightly closed. Keep cool(2 ~ 10°C).
INCOMPATIBLE PRODUCTS	: Strong oxidizers, acids

8. EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING MEASURES	: Use exhaust ventilation to keep airborne concentrations below exposure limits. Use adequate ventilation.
VENTILATION	: Local Exhaust ; Necessary, Mechanical(General) ; Necessary
CONTROL PARAMETERS	
ACGIH	: TWA 150 ppm
OSHA	: TWA 150 ppm
NIOSH	: TWA 150 ppm
PERSONAL PROTECTION	
RESPIRATORY PROTECTION	: Use respirators approved under appropriate government standards and follow all regulations.
HAND PROTECTION	: Chemical resistant gloves
EYE PROTECTION	: Safety glasses(goggles)
SKIN PROTECTION	: Protective clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	: Colorless, clear liquid
ODOR	: Characteristic odor
pH	: No data available
BOILING POINT	: approx.126.1 °C
MELTING POINT	: -78 °C
FLASH POINT	: 22 °C (TCC)
EXPLOSIVE LIMITS	: 1.2 ~ 7.6 vol %
VAPOR PRESSURE	: 1.2 kPa (at 20°C)
VAPOR DENSITY	: 4.0
SPECIFIC GRAVITY	: 0.8826 g/cm ³ (at 20/20°C)
SOLUBILITY IN	
Water	: Miscible
Organic solvent	: Miscible
PARTITION COEFFICIENT ; n-octanol/water	: log Pow: 1.82
AUTOIGNITION TEMPERATURE	: 425 °C
DECOMPOSITION TEMPERATURE	: No data available

10. STABILITY AND REACTIVITY

REACTIVITY	: Stable under recommended storage conditions.
CHEMICAL STABILITY	: Deteriorated by sun-light.
CONDITION TO AVOID	: Sunlight, heat, open flames, high temperature, sparks, static electrical charge, other ignition sources, moisture
INCOMPATIBLE MATERIALS	: Oxidizers and strong acids
HAZARDOUS DECOMPOSITION PRODUCTS	: CO, CO ₂ may be formed.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY	: Oral; rat LD50=3,200 ~ 14,130 mg/kg (SIDS,2009 etc.) Dermal; rabbit LC50= > 5,000 ~ > 17,600mg/kg (ACGIH(7th,2001) etc.) Inhalation; rat LC50=2,000 ~ > 8,000 ppm (ACGIH(7th,2001) etc.)
SKIN CORROSION/IRRITATION	: Rabbit/Human; Negative (SIDS,2009)
EYE DAMAGE/EYE IRRITATION	: Rabbit; mild to moderate irritating. Human; slightly mild eye irritating (SDIS,2009)
SENSITIZATION	: No data available
GERM CELL MUTAGENICITY	: in vitro; negative. (SIDS,2009 etc.)
CARCINOGENICITY	: No data available
REPRODUCTIVE TOXICITY	: Lack of data
SPECIFIC TARGET ORGAN TOXICITY - single exposure -	: This material has a respiratory irritation. Effect to human (headache, dizziness, nausea, dyspnea, loss of consciousness and weakness).
SPECIFIC TARGET ORGAN TOXICITY - repeated exposure -	: Lack of data
ASPIRATION HAZARD	: No data available

12. ECOLOGICAL INFORMATION

ECOTOXICITY : Pimephales promelas; LC50=18 mg/L,96h (CICAD 64(20059, SIDS(2009))
BIODEGRADABILITY : BOD=98 % (SIDS,2009)
BIOACCUMULATIVE POTENTIAL : Log Kow=1.78 (PHYSPROP Database, 2009)
MOBILITY IN SOIL : No data available
OTHER ADVERSE EFFECTS : Not listed in Montreal Protocol list.

13. DISPOSAL INFORMATION

Dispose in a hazardous-waste site in accordance with all applicable regulations. Any disposal practice must be in compliance with country, local, state, and federal laws and regulations (contact country, local or state environment agency for specific rules).

14. TRANSPORT INFORMATION

IATA

UN NUMBER : 1123
UN PROPER SHIPPING NAME : Butyl acetate
CLASS : 3, flammable liquid
PACKING GROUP : II
ADR/RID : 1123, Butyl acetate, II
DOT : 1123, Butyl acetate, II
MARINE POLLUTANT : No

15. REGULATORY INFORMATION

US REGULATIONS : Labeling according to EC Directives; See section 2
EU REGULATIONS : Labeling according to EC Directives; See section 2

16. OTHER INFORMATION

NOTICE:

The information contained in the SDS description is applicable exclusively to the chemical substance identified herein and for its intended use as an analytical reference standard or reagent and to the unit quantity intended for that purpose. The information does not relate to, and may not be appropriate for, any application or larger quantity of the substance described. Our products are intended for the use by individuals possessing sufficient technical skill and qualification on use the material potential hazardous chemical. Accordingly, no representation or warranty, express or implied, with respect to merchantability and fitness for a particular purpose is made with respect to the information contained herein.

Attention:

This product in terms of chemical identity and the unit amount provide is intended for use in chemical analysis and not for human consumption, nor any other purpose.